

# Safety Data Sheet

## SECTION I - IDENTIFICATION

**PRODUCT NAME:** Brilliance  
**PRODUCT CODE:** 2490  
**PRODUCT USE:** Steel and Metal Polish  
**COMPANY NAME:** QuestSpecialty Corporation  
**COMPANY ADDRESS:** PO Box 624 Brenham, TX 77834  
**COMPANY PHONE:** 1-800-231-0454  
**EMERGENCY PHONE:** 800-255-3924

## SECTION II – HAZARDS IDENTIFICATION

**CLASSIFICATION:** Flammable Aerosol: Category 2

Liquefied Gas

Eye Irritant: Category 2b

Aspiration Hazard: Category 1

**HAZARD STATEMENT(S): DANGER:** Flammable Aerosol Contains gas under pressure; May explode if heated. Causes eye irritation. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



**SYMBOL:**

**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

## SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Isoparaffinic Hydrocarbon	64742-47-8	40-70%
Propane/n-Butane	68476-86-8	10-30%
White Mineral Oil	8042-47-5	10-30%
Fragrance Oil	Mixture	1-5%

## SECTION IV - FIRST AID MEASURES

**EYES:** Immediately flush with water for 15 - 20 minutes while holding eyelids open. Seek medical attention if irritation persists.

**INGESTION:** Immediately call a poison center or doctor. Do NOT induce vomiting.

**INHALATION:** Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

**SKIN:** Immediately wash with soap and water for 15 minutes. Seek medical attention if irritation develops.

**ACUTE HEALTH HAZARDS:** Eye: stinging, tearing, redness

Oral: Aspiration risk

**CHRONIC HEALTH HAZARDS:** None known

**NOTE TO PHYSICIAN:** There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

## SECTION V – FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Carbon dioxide, foam, and water fog.

**UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream.

## Safety Data Sheet

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon

### SECTION VI – ACCIDENTAL RELEASE MEASURES

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Stop leak if you can do so without risk. Move the cylinder/can to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent spill from entering sewers, storm drains, and natural waterways. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations.

**RCRA STATUS:** Waste likely considered non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### SECTION VII – HANDLING AND STORAGE

**HANDLING AND STORAGE:** Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

**OTHER PRECAUTIONS:** Keep out of the reach of children.

**INCOMPATIBILITY:** Some plastics and painted surfaces, pre-test before using.

### SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Isoparaffinic Hydrocarbon	400 ppm	400 ppm
Propane/n-Butane	1000 ppm	1000 ppm
White Mineral Oil	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>
Fragrance Oil	Not Established	Not Established

**ENGINEERING CONTROLS / VENTILATION:** Ambient ventilation adequate.

**RESPIRATORY PROTECTION:** Not required with normal use.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses

**ADDITIONAL MEASURES:** Wash hands thoroughly after handling.

### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** Clear Aerosol

**ODOR:** Lemon scent

**ODOR THRESHOLD:** N/D

**BOILING POINT:** N/D

**FREEZING POINT:** N/D

**FLAMMABILITY:** Flammable Aerosol

**FLASH POINT:** N/D

**AUTOIGNITION TEMPERATURE:** N/D

**LOWER FLAMMABILITY LIMIT:** N/D

**UPPER FLAMMABILITY LIMIT:** N/D

**VAPOR PRESSURE (mm Hg):** 0.5 @ 77°F (25°C)

**VAPOR DENSITY (AIR=1):** > 1

**EVAPORATION RATE:** 0.2

**SPECIFIC GRAVITY (H<sub>2</sub>O=1):** 0.82

**pH:** N/A

**SOLIDS (%):** N/D

**SOLUBILITY IN WATER:** 0%



# Safety Data Sheet

**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN 1950

**SHIPPING BY WATER:**

**VESSEL (IMO/IMDG)**  
**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN 1950  
**ENVIRONMENTAL HAZARDS WATER:** N/A

## SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:** All Chemicals are listed or exempt.  
**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** None  
**SARA 311/312 HAZARD CATEGORIES:** None  
**SARA 313 REPORTABLE INGREDIENTS:** None  
**STATE REGULATIONS:** California Proposition 65: None  
**INTERNATIONAL REGULATIONS:** Isoparaffinic Hydrocarbon (64742-47-8)

<b>NFPA HEALTH:</b>	1	<b>HMIS HEALTH:</b>	1
<b>NFPA FLAMMABILITY:</b>	3	<b>HMIS FLAMMABILITY:</b>	3
<b>NFPA REACTIVITY:</b>	0	<b>HMIS REACTIVITY:</b>	0
<b>NFPA OTHER:</b>	None	<b>HMIS PROTECTION:</b>	A

## SECTION XVI - ADDITIONAL INFORMATION

**PREPARATION BY:** Jonathon Jarvis      **DATE PREPARED:** 12/23/2013      **REVISION DATE:** 11/24/2015

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.